

STANDARD DELIEVERY

| Main unit | 1pc |
|---------------|-----|
| 32G SD card | 1pc |
| Card reader | 1pc |
| USB cable | 1pc |
| Tripod | 1pc |
| AC/DC adapter | 1pc |

OPERATING ENVIRONMENT


Weight

| Main unit | -10~50°C, no preheat |
|-----------------------|------------------------------|
| Operating temperature | -20~70°C |
| Storage temperature | -20~60°C |
| Relative humidity | maximum 90%, no condensation |

1000g

OPTIONAL ACCESSORY

| Cable | Please refer to next pages for details | | | | | | | |
|-------------------|---|--|--|--|--|--|--|--|
| WIFI output | ISV-S-WIFI(must be installed in factory, only for android OS) | | | | | | | |
| Temperature alarm | ISV-S-HTALARM(must be installed in factory, for Ø3.9mm, Ø4.5mm and Ø6.0mm | | | | | | | |
| | ISV-S-CLAMP1, ISV-S-CLAMP2, ISV-S-CLAMP3, ISV-S-CLAMP4 | | | | | | | |
| Clamp | (must be installed in factory, for Ø3.9mm, Ø4.5mm and Ø6.0mm) | | | | | | | |



FOUR-DIRECTION CABLE, FRONT VIEW&SIDE VIEW

| | Cable | | Lens | | | | | | | | | |
|-----------|--------|-------------------------------|-------------------|--------------------|-----------------|------------------------|-------|---------------------|--------------|-------|------------|---------------------|
| Code | length | type | view direction | bend direction | diameter (D) | depth of field(DOF) | | angle of view(θ) | illumination | pixel | resolution | dust/ waterproof |
| ISV-S6010 | 1m | tungsten wire weaved cable | | four directions | 6.0mm | front view: | | 60° >120° | rear fiber | 0.92M | 1280×720 | IP67 |
| ISV-S6015 | 1.5m | | | | | 12~200mm (optional | | | | | | |
| ISV-S6020 | 2m | | | | | 3~70mm) | | | | | | |
| ISV-S6030 | | | | | | side view: | ±160° | | | | | |
| ISV-S6040 | 4m | | | | | 8~150mm (optional | | | | | | |
| ISV-S6050 | 5m | | | | | 3~70mm) | | | | | | |