IMPACT TESTER CODE THD-PF34

- For paint and varnish dry coating. To test the ability to resist cracking or peeling from the substrate when deformation is caused by weights impact under standard conditions
- Indenter, base and weight can be replaced quickly
- Conform to ISO 6272-2:2002, ASTM D 2794





SPCIFICATION

51 611 167 (1161)		
Impact height range	0-100cm (0-40inch)	
Graduation	1cm	
Impact depth	2.5cm	
Weight	1000g (2pcs), 300g (1pc), 2lb (2pcs)	
Indenter diameter	Ø12.7mm (1/2 inch DIA), Ø15.9mm (5/8 inch DIA)	
Die base diameter	Ø16.3mm	







1000g main weight

300g main weight

2lb main weight

STANDARD DELIVERY

STANDARD DELIVERT	
Main unit	1pc
1000g main weight	1pc
300g main weight	1pc
2lb main weight	1pc
1000g additional weight	1pc
2lb additional weight	1pc
Ø12.7mm indenter	1pc
Ø15.9mm indenter	1pc
Ø16.3mm die base	1pc







1000g additional weight 2lb additional weight Ø12.7mm indenter

OPTIONAL DELIVERY

Base plate [*]	THD-PF34-T	Size: 120×70×0.5mm 180 pieces/box
-------------------------	------------	--------------------------------------

 $^{{}^{}ullet}$ Can be customized according to the needs of different thickness, size and processing



Ø15.9mm indenter



Ø16.3mm die base