

DC POWER SUPPLY CODE 9911-PS305

- Four-digit LED display
- Output power display
- Output switch control
- 10mV/1mA high accuracy and resolution
- Panel locking function to prevent misoperation
- USB interface for power supply
- OVP/OCP protection
- 3 shortcut keys for presetting



test leads (included)

SPECIFICATION

Voltage	Range	30V
	Setting resolution	10mV
	Setting accuracy	$\leq 0.1\% + 10\text{mV}$
	Readback resolution	10mV
	Readback accuracy	$\leq 0.1\% + 10\text{mV}$
	Load regulation	$\leq 0.1\% + 5\text{mV}$
	Line regulation	$\leq 0.01\% + 5\text{mV}$
	Ripple	10mVrms
Current	Range	5A
	Setting resolution	1mA
	Setting accuracy	$\leq 0.2\% + 3\text{mA}$
	Readback resolution	1mA
	Readback accuracy	$\leq 0.2\% + 3\text{mA}$
	Load regulation	$\leq 0.2\% + 3\text{mA}$
	Line regulation	$\leq 0.2\% + 3\text{mA}$
	Ripple	8mArms
OVP		0~33V
OCP		0~5.5A
Work condition		temperature: 0~40°C, humidity: $\leq 80\%$ RH
Storage condition		temperature: -20~60°C, humidity: $\leq 80\%$ RH
Cool system		fan cool
Power supply		AC: 220V $\pm 10\%$, 50Hz/60Hz
Dimension (LxWxH)		230x80x150mm
Weight		1.45kg

STANDARD DELIVERY

Main unit	1 pc
Test lead	2 pcs