BLACK AND WHITE DENSITOMETER CODE RXT-BM301

- With accurate reading, good stability, easy to operate
- Small size, light weight, 27 LED lighting source, good shock resistance
- Comes with calibration software and standard black and white density film, allowing self calibration of instruments
- Suitable for industries such as non-destructive testing, photosensitive materials, printing, etc





black and white density film(0.0~5.0) (included)

SPECIFICATION

Blackness range	D=0.00~5.00	
Reading stability	±0.02	
Accuracy	±0.02 (0.0 <d≤2.0) ±1% (2.0<d≤4.0) ±0.05 (4.0<d≤5.0)< th=""></d≤5.0)<></d≤4.0) </d≤2.0) 	
Optical aperture	Ø2mm	
Sampling time	0.8s	
Display form	three-digit display	
Interface	Rs232 (optional accessory USB cable)	
Operation environment	0°C~40°C, relative humidity ≤85%	
Power supply	220V, 50/60Hz	
Dimension	260×265×110mm	
Weight	2.1kg	

STANDARD DELIVERY

Main unit	1pc
Black and white density film (0.0~5.0)	1pc
USB flash disk	1pc
RS232 cable	1pc

OPTIONAL ACCESSORY

USB cable	RXT-BM301-CA